

SECTION A: ANNUAL SPECIFICATIONS



INSTRUCTIONS:

- ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
- FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
 - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
- COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
			Yes: <input type="checkbox"/>	No: <input type="checkbox"/>	
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than 1/4" beyond of the approach side of the foul line.	Yes: <input type="checkbox"/>	No: <input checked="" type="checkbox"/>	5 & 6
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

				Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	
				1	2	3	4	5	6	7	8	9	10	---	---
5	Kickback Plate to Kickback Plate (at rear row of pins)			59 5/8	59 3/4	59 3/4	59 3/4	59 3/4	59 7/8	59 3/4	59 3/4	59 5/8	59 3/4		
	Spec Range:	59 5/8"	60"												
6	Crosswise Tilt (at rear row of pins)			⁷ / ₁₀ 0	⁷ / ₁₀ 030	⁷ / ₁₀ 0	⁷ / ₁₀ 020	⁷ / ₁₀ 010	⁷ / ₁₀ 0	⁷ / ₁₀ 010	⁷ / ₁₀ 020	⁷ / ₁₀ 020	⁷ / ₁₀ 020	⁷ / ₁₀	⁷ / ₁₀
	Spec Range:	-0.040"	0.040"												
7	Lengthwise Tilt		Between 4-7 pins	^F / _P 135	^F / _P 0	^F / _P 020	^F / _P 120	^F / _P 080	^F / _P 145	^F / _P 135	^F / _P 095	^F / _P 105	^F / _P 155	^F / _P	^F / _P
	Spec Range:	-0.187"	0.187"	Between 6-10 pins	^F / _P 135	^F / _P 090	^F / _P 040	^F / _P 120	^F / _P 145	^F / _P 135	^F / _P 135	^F / _P 095	^F / _P 135	^F / _P 170	^F / _P
8	Gutter Depth (at rear row of pins)			7 pin	3 3/8	3 5/8	3 3/8	3 5/8	3 1/2	3 1/2	3 1/2	3 5/8	3 3/8	3 3/8	
	Spec Range:	3 3/8"	3 5/8"	10 pin	3 1/2	3 5/8	3 3/8	3 1/2	3 5/8	3 5/8	3 1/2	3 1/2	3 1/2	3 5/8	