

# SECTION A: ANNUAL SPECIFICATIONS



## INSTRUCTIONS:

1. ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
2. FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
  - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
3. COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

**NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.**

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than ¼" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

			Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.
			49	50	---	---	---	---	---	---	---	---	---
5	Kickback Plate to Kickback Plate (at rear row of pins)		59 3/4	59 3/4									
	Spec Range:	59 5/8"    60"											
6	Crosswise Tilt (at rear row of pins)		7 10 20	7 10 0	7 10	7 10	7 10	7 10	7 10	7 10	7 10	7 10	7 10
	Spec Range:	-0.040"    0.040"											
7	Lengthwise Tilt		Between 4-7 pins	F P 030	F P 040	F P	F P	F P	F P	F P	F P	F P	F P
	Spec Range:	-0.187"    0.187"	Between 6-10 pins	F P 040	F P 050	F P	F P	F P	F P	F P	F P	F P	F P
8	Gutter Depth (at rear row of pins)		7 pin	3 3/8	3 3/8								
	Spec Range:	3 3/8"    3 5/8"	10 pin	3 3/8	3 3/8								